







ZAWIESIA LINOWE wg PN-EN 13414-1 + A2

Współczynnik bezpieczeństwa 1:5

	1-ciężnowe	2-ciężnowe		3- i 4-ciężnowe	
					
Średnica liny [mm]	DOR tony	DOR tony 0 - 45°	DOR tony 45 - 60°	DOR tony 0 - 45°	DOR tony 45 - 60°
6	0,40	0,50	0,40	0,80	0,60
8	0,75	1,05	0,75	1,55	1,10
9	0,85	1,20	0,85	1,80	1,30
10	1,15	1,65	1,15	2,45	1,75
11	1,40	2,00	1,40	3,00	2,15
12	1,70	2,35	1,70	3,55	2,55
13	2,00	2,80	2,00	4,20	3,00
14	2,30	3,25	2,30	4,85	3,45
16	3,00	4,25	3,00	6,40	4,55
18	3,85	5,40	3,85	8,00	5,70
20	4,75	6,60	4,75	9,90	7,10
22	5,70	8,00	5,70	12,00	8,60
24	6,80	9,55	6,80	14,35	10,25
26	8,00	11,20	8,00	16,80	12,00
28	9,30	13,00	9,30	19,50	13,95
30	10,65	15,00	10,65	22,40	15,90
32	12,15	17,00	12,15	25,50	18,20
36	15,35	21,50	15,35	32,30	23,00
40	19,00	26,70	19,00	38,30	28,50