

ZAWIESIA ŁAŃCUCHOWE INOX ze stali nierdzewnej

klasa 5


Współczynnik bezpieczeństwa 1:4




1-ciężnowe



2-ciężnowe



3- i 4-ciężnowe



Bezkońcowe



Pętlowe



Średnica
łańcucha
[mm]

DOR
tony
0°

DOR
tony
0 - 45°

DOR
tony
45 - 60°

DOR
tony
0 - 45°

DOR
tony
45 - 60°

DOR
tony
0°

DOR
tony
0 - 45°

DOR
tony
0 - 45°

4

0,320

0,450

0,320

0,670

0,475

0,512

0,450

0,670

5

0,500

0,700

0,500

1,050

0,750

0,800

0,700

1,050

6

0,750

1,000

0,750

1,600

1,120

1,200

1,000

1,600

7

1,000

1,400

1,000

2,100

1,500

1,600

1,400

2,100

8

1,250

1,700

1,250

2,650

1,800

2,000

1,700

2,650

10

2,000

2,800

2,000

4,250

3,000

3,200

2,800

4,250

13

3,200

4,500

3,200

6,700

4,750

5,120

4,500

6,700

16

4,500

6,300

4,500

9,450

6,750

8,000

6,300

9,450