

ZAWIESIA ŁAŃCUCHOWE wg PN-EN 818-4

klasa 10

Współczynnik bezpieczeństwa 1:4




1-cięgnowe

2-cięgnowe

3- i 4-cięgnowe

Bezkońcowe

Pętlowe



Średnica
łańcucha
[mm]

DOR
tony
0°

DOR
tony
0 - 45°

DOR
tony
45 - 60°

DOR
tony
0 - 45°

DOR
tony
45 - 60°

DOR
tony
0°

DOR
tony
0 - 45°

DOR
tony
0 - 45°

6

1,40

2,00

1,40

3,00

2,12

2,24

2,00

3,00

7

1,90

2,65

1,90

4,00

2,80

3,00

2,65

4,00

8

2,50

3,55

2,50

5,30

3,75

4,00

3,55

5,30

10

4,00

5,60

4,00

8,00

6,00

6,30

5,60

8,00

13

6,70

9,50

6,70

14,00

10,00

10,60

9,50

14,00

16

10,00

14,00

10,00

21,20

15,00

16,00

14,00

21,20

19

14,00

20,00

14,00

30,00

21,20

22,40

20,00

30,00

22

19,00

26,50

19,00

40,00

28,00

30,00

26,50

40,00

26

26,50

37,50

26,50

56,00

40,00

42,50

37,50

56,00

32

40,00

56,00

40,00

85,00

60,00

63,00

56,00

85,00